



SAFETY FOR YOUR LIFE



MB FOAM SYSTEM

128 Luong The Vinh -St
Tan Thoi Hoa Ward
Tan Phu Dist HCM City
Vietnam
Tel : 84-8-39611082
Fax : 84-8-38762198
www.minhbao.com.vn

Name: Concealed Fire Sprinkler
 Model NO.: ZSTDY15
 Size (mm): 15(1/2")
 Connecting Thread (Inch): R(1/2")
 K-Factor: 80(5.57@US)
 Rated Working Pressure : 0.35Mpa



Name: Fusible Alloy Fire Sprinkler
 Model NO.: ZSTY
 Size (mm): 15(1/2")/20(3/4")
 Connecting Thread (Inch): R(1/2")/R(3/4")
 K-Factor: 80(5.57@US)/150(8.05@US)
 Rated Working Pressure : 0.35Mpa



Name: ESFR Fire Sprinkler
 Model NO.: ESFR20
 Size (mm): 15(1/2")
 Connecting Thread (Inch): R(1/2")
 K-Factor: 80(5.57@US)
 Rated Working Pressure : 0.35Mpa
 Glass Bulb: 3mm



Name: Foam Fire Sprinkler
 Model NO.: PT15
 Size (mm): 15(1/2")
 Connecting Thread (Inch): R(1/2")
 K-Factor: 42(2.93@US)
 Rated Working Pressure : 0.4Mpa
 Foaming Level: ≥5
 25% Dissection Time ≥120s



Name: Foam Fire Sprinkler
 Model NO.: TY-PT15
 Size (mm): 15(1/2")
 Connecting Thread (Inch): R(1/2")
 K-Factor: 42(2.93@US)
 Rated Working Pressure : 0.4Mpa
 Foaming Level: ≥5
 25% Dissection Time ≥120s



Name: Pendent Water Curtain Fire Sprinkler
 Model NO.: ZSTMA
 Size (mm): 15(1/2")/20(3/4")/25(1")
 Min Working Pressure : 0.1Mpa
 Spray Angle: 90°/120°/160°



Name: Water Fog Fire Sprinkler
 Model NO.: ZSTW
 Size (mm): 15(1/2")/20(3/4")/25(1")
 Rated Working Pressure : 0.35Mpa
 Spray Angle: 60°/90°/120°



Name: Horizontal Water Curtain Fire Sprinkler
 Model NO.: ZSTMB
 Size (mm): 15(1/2")/20(3/4")/25(1")
 Min Working Pressure : 0.1Mpa
 Spray Angle: 90°/120°/160°



Name: Water Fog Fire Sprinkler
 Model NO.: ZSTWB
 Size (mm): 15(1/2")/20(3/4")/25(1")
 Rated Working Pressure : 0.35Mpa
 Spray Angle: 60°/90°/120°



Name: Impact Water Fog Fire Sprinkler
 Model NO.: ZSTWC
 Size (mm): 15(1/2")/20(3/4")/25(1")
 Rated Working Pressure : 0.35Mpa
 Spray Angle: 60°/90°/120°



Foam Bladder Tank

Name:Vertical Foam Bladder Tank
Model NO.:PHYML
Volume (L):500-13000
Proportion Of Mixture:3% Or 6%
Max Flow Rate:80L/S
Rated Working Pressure :0.8Mpa
Material:Carbon Steel



Name:Horizontal Foam Bladder Tank
Model NO.:PHYM
Volume (L):500-13000
Proportion Of Mixture:3% Or 6%
Max Flow Rate:80L/S
Rated Working Pressure :0.8Mpa
Material:Carbon Steel



Name:Vertical Foam Chamber
Model NO.:PCL
Rate Of Flow(L/S):4 /8 /16 /24
Working Pressure :0.3-0.6Mpa
Foaming Level: ≥ 6
25% Dissection Time ≥ 150 s



Name:Horizontal Foam Chamber
Model NO.:PC
Rate Of Flow(L/S):4 /8 /16 /24
Working Pressure :0.3-0.6Mpa
Foaming Level: ≥ 6
25% Dissection Time ≥ 150 s



Name:Foam Nozzle
Model NO.:PQ
Rate Of Flow(L/S):4 /8 /16
Connecting :Male Storz Coupling 65mm
Jetting Range: 24 /28 /32
Rated Working Pressure :0.7Mpa



Name:Mobile Foam Unit
Model NO.:PY
Capacity (L):50 /100 /200 /300 /400 /500
Rate Of Flow(L/S): 4 /8
Working Pressure :0.5-1.2Mpa



Name:Foam Concentrate
Model NO.:AFFF
Concentration:3% /6%
Compatibility:Water /Sea Water
PH:7-8.5
Package:200KGS/Barrel



Fire Monitor



Name:Manual Fire Water Monitor
 Model NO.:PS
 Rate Of Flow(L/S):20 /30 /40 /50 /60
 Jetting Range: ≥ 48 /55 /60 /65 /70
 Rated Working Pressure :0.8Mpa
 Horizontal Turning Angle:0-360
 Depression&Elevation Turning Angle:70

Name:Mobile Fire Water Monitor
 Model NO.:PSY-A
 Rate Of Flow(L/S):40
 Jetting Range(m): ≥ 60
 Rated Working Pressure :1.0Mpa
 Horizontal Turning Angle: ± 10 / ± 15 / ± 20
 Depression&Elevation Turning Angle:10-50



Name:Mobile Fire Water Monitor
 Model NO.:PSY-B
 Rate Of Flow(L/S):80
 Jetting Range(m): ≥ 75
 Rated Working Pressure :1.0Mpa
 Horizontal Turning Angle:0-90
 Depression&Elevation Turning Angle:360



Name:Manual Fire Water Monitor
 Model NO.:PST
 Rate Of Flow(L/S):24 /32 /48 /64
 Water Jetting Range: ≥ 45 /50 /55 /60
 Foam Jetting Range: ≥ 40 /45 /55 /60
 Working Pressure :0.6-1Mpa
 Horizontal Turning Angle:0-360
 Depression&Elevation Turning Angle:-35-90



Fire Alarm Valve



Name:Alarm Wet Valve
 Model NO.:ZSFZ
 Size(mm):50 /100 /150 /200
 Size(Inch):2" /4" /6" /8"
 Working Pressure :1.2Mpa
 Material:Ductile Iron

Name:Alarm Deluge Valve
 Model NO.:ZSFM
 Size(mm):50 /65 /80/100 /150 /200
 Size(Inch):2" /2.5"/3" /4" /6" /8"
 Working Pressure :1.2Mpa
 Material:Ductile Iron



Name:Pre-Action Alarm Valve
 Model NO.:ZSFY
 Size(mm):100 /150 /200
 Size(Inch):4" /6" /8"
 Working Pressure :1.2Mpa
 Material:Ductile Iron



Name:Level Type Alarm Deluge Valve
 Model NO.:ZSFG
 Size(mm):50 /100 /150 /200
 Size(Inch):2" /4" /6" /8"
 Working Pressure :1.2Mpa
 Material:Ductile Iron

